







Top or Bottom MICR

Easy Paper Loading

Easy ribbon replacement


- High Speed: 250mm/sec (the fastest speed in the industry for hybrid)
- Affordable Price: **Key functions and** high quality graphics



HSP7000 - The Functions You Need At The Price You Can Afford

Star Micronics is proud to announce another addition to its extensive product line of POS printers. The multifunction (hybrid), HSP7000.

The HSP7000 is designed to assist and empower users who want to extend the capabilities of their





- Read the check's MICR reliably
- Endorse checks without jams
- Print a receipt as fast as possible

The HSP7000 combines key features from Star's celebrated range of products, including the speed and reliability of the market leading TSP700 Series, and the engine from the high speed SP700 dot matrix printer. Star is bringing over 30 years of "know-how" in POS to the HSP7000; resulting in customers receiving the features they need with the reliability they demand, minus the overhead of unnecessary features and cost.




Slip/Endorsement Station

Validation Station

## Quick Specs:

- Fast 250mm/sec thermal receipt printing
- Drop-in paper loading
- Print high quality graphics, high speed slip station (with built-in forms stopper)
- Standard printer dimensions allow for easy "drop-in" replacement of competitor hybrid printer.









## **HSP7000 Specifications**

	The Complete Hybrid Solution!	
Features	Hardware  Ultra Fast receipt print (250mm/s)  "Drop-In & Print" Clamshell Design  Quick Check Processing w/ MICR Reader Fast and Easy Validation  Reliable Guillotine Cutter  Small Footprint  PDF417 Barcode Support (Receipt)  Double Resolution Mode Support  Two Color Receipt Print Capable  Swappable Communication Interface  WHQL Certified  Recessed Cable Connections  ESC/POS™ emulation supported	Software Logo Utility (Store Logos, Coupons, and Graphics) Memory Switch Configuration Setup Utility Ethernet Interface Setup Utility Create a Virtual Serial Port for legacy applications
Connectivity  Note: Connections in <b>bold</b> are supported; grayed-out connection types may be	9-pin serial 25-pin serial Parallel USB Powered USB Dual 9-PinSerial/USB Ethernet	Virtual Serial Port to USB Virtual Serial Port to Ethernet
supported by special request.	Wi-Fi	
Drivers  Note: Drivers in <b>bold</b> are immediately available; grayed-out operating systems may be supported by special request.	Windows 98, ME NT 4.0 WEPOS 2000, XP CE XP Embedded VISTA (32 bit / 64 bit)	OPOS Java POS Linux CUPS Mac OSX CUPS
What's Included	Installation CD (Printer Driver / Manuals) Setup Sheet Interface Cover Paper Guide for 76mm / 58mm Width	Power Switch Cover Ferrite Core Ink Ribbon Cartridge Start up Paper Roll
Options	External Power Supply (PS60A) Putty or Gray Color Powered USB Cable	No MICR Version Reader Model Available MICR Top Position (optional) MICR Bottom Position (standard)
Technical Specifications  Thermal Receipt Station	Print Method: Direct Thermal Print Speed: 250mm/s Paper Width: 80mm / 76mm / 58mm Paper Thickness: 0.065 to 0.085mm Paper Diameter: Max 83mm	Resolution: 203 dpi MCBF: 60 Million Lines Cutter: 1.5 Million Cuts Emulation : Star Line Mode, ESC/POS™
Slip/ Endorsement Station	Print Method: 9 Pin Impact Dot Matrix Print Speed: 4.82 lps (40 columns) Columns: 60/45 Paper Width: 68mm to 230mm Paper Length: 75mm to 297mm	Paper Thickness: 0.09 to 0.2mm (Single-ply paper) Less than 0.31mm (Multi-ply paper) Copy Capacity: Original + 3 copies MCBF: 37 Million Lines Emulation: Star Mode, ESC/POS™
Validation Station	Lines : Max 8 Lines	
MICR Reader	Character Set: E13B / CMC-7	
	Power: DC24V Dimensions: W=186mm, H=177mm, D=296mm	Weight: 4.6kg
Warranty	For US and Canada: 3-year Limited Warranty, plus optional Extended Services Agreement Policies (Extend-A-Star and Swap-A-Star)	
For Further Information	Sales: 1-800-782-7636 x107 Technical Support: 1-800-782-7636 x105	Web: http://www.starmicronics.com

