

## Product Profile



- Lightweight, ergonomic design allows for single-handed operation
- Choices of integrated bar code scanner or imager
- Large 160 x 160 display for flexibility in application design
- Customize with a flexible rapid development tool
- Linux® based operating system
- Powerful 67 MHz processor to support large look-up tables or data storage
- Choice of data communication docks

### CK1 HANDHELD COMPUTER

Companies of all sizes can now realize the benefits of automatic data collection with the CK1, a powerful and flexible batch data collection terminal for retail, light industrial, and medical/pharmaceutical applications requiring small-sized ergonomics at an economical price. With choices of simplified programming tools or pre-loaded applications, linear imager or bar code scanner, along with large memory and a crisp display, Intermec's CK1 can benefit the bottom line through increased employee productivity and inventory accuracy.

The CK1 offers features and functionality found in terminals much larger and more costly. With an ergonomic keyboard and a pocket-sized form factor, the CK1 allows for easy single-handed operation when it is demanded. An optional removable pistol grip handle is available for scan intensive applications.

The CK1 has a choice of bar code input options: an integrated laser scanner, or a highly responsive linear imager, offering safe user interaction and aggressive decoding performance. The large, scratch-resistant 160 x 160 pixel display with backlight provides user-friendly navigation in all lighting conditions, as

well as flexibility in application design. Continuing the Intermec legacy of rugged construction, the CK1 withstands multiple 1.2-meter (4-ft) drops to a hard surface.

Users will appreciate the simplicity of pre-written batch applications, powerful rapid application development tools or extensive SDK for flexible application choices offered by the CK1. It combines a Linux® based operating system and Linux® programming tools to provide a powerful and flexible open source platform for rich end-user applications with multi-tasking capabilities. Use CK1 right out of the box with pre-written programs for various applications, or for powerful and rapid application development, a Windows® based rapid development tool can be purchased that requires no programming experience.

Intermec's CK1 has a powerful ARM 7, 67 MHz processor with 16MB DRAM and 9MB Flash to support large look-up tables or data storage. A replaceable Lithium-Ion battery supports extended rigorous use and a fast 3-hour recharge.

Numerous docking options are available including a single-slot RS-232 or modem dock and a multi-slot USB charging dock.

**Physical Description**

The ergonomic, pocket-sized CK1 is a fully functional Linux based computer for efficient, automated batch data collection. With large display, and choice of integrated bar code scanner or linear imager, the CK1 is ideal for parcel pickup and delivery, light industrial, and retail inventory management.

**Physical Characteristics**

**Length:** 190 mm (7.5")

**Height:** 35 mm (1.35")

**Width:** 73 mm (2.88")

**Depth:** N/A

**Weight:** 218 g (7.68 oz.) including battery

**Power**

**Supply:** 900 mAh (3.6V) rechargeable

Lithium Ion (Li-Ion) battery pack

**Battery Life:** Extended shift (12 hour)

**Power Management:** Auto-suspend

**AC Adapter/Recharging:** 3-4 hour recharge time

**Environment**

**Operating Temperature:** -10° to 60° C

(14° to 140° F)

**Storage Temperature:** -20° to 70° C

(-4° to 158° F)

**Recharging Temperature:** 0° to 50° C

(32° to 122° F)

**Humidity:** 0 to 95% relative humidity (non-condensing)

**Rain and Dust Resistance:** IP40

**Drop Survival:** Designed for multiple 1.2m (4-ft) drops to concrete

**Hardware**

**Memory:** 16MB DRAM

**Non-volatile Flash Memory:** 9MB

**Microprocessor:** 67 MHz ARM 7 Processor

**Operating System:** Embedded Linux

Operating System, EsFia uCLinux

Version 2.4

**Display:** Monochrome, anti-glare LCD display capable of configurable graphics and supporting up to 16 lines by 20 characters (160 x 160 pixels) with auto-off EL backlighting and scratch resistance surface.

**Keyboard:** 29 hard top keys including single Enter/Scan button, Numeric keys, with shift alpha, 4 navigation keys and 4 function keys

**Beeper:** User programmable volume, pitch and duration

**LED:** Tri-state software programmable LED to indicate good/bad read/communication

**Software****Development Environments:**

Microsoft® C application development under Windows 2000, XP

Software Development Kit (SDK)

MCL Rapid Development Tool Kit for

application program development

**International Support**

English / Western European languages

Japanese, Traditional Chinese (Big 5),

Chinese Simplified, Thai (future)

**Connectivity**

**TCP/IP over PPP using the following transports:** RS232 direct single dock, USB multi dock, RS232 modem or \*Bluetooth™.

TCP/IP over PPP GPRS using either a Bluetooth or tethered GPRS mobile phone.

Z-Modem communication protocols using either RS232 direct single dock, USB multi dock, RS232 modem or Bluetooth.

**Security**

Administrative password protection optional

**Bar Code Symbolologies**

Code 39 Standard and Full ASCII, Codabar, UPC/EAN, UCC/EAN128, Interleaved 2 of 5, Code 32, Standard 2 of 5, Code 93, Code 128, MSI, Plessey, China Postal Code, RSS14

**Characters/Fonts**

Font 1: Courier 6x8, 20 lines, 26 columns

Font 2: Courier 8x16, 10 lines, 20 columns

**Bar Code Scanning Module Options**

Integrated Linear Imager

Integrated Standard Range Visible Laser (650nm)

**Scanning Performance**

**Scan rate:** Linear Imager – 270 scans/second

**Scan rate:** Visible Laser – 39 scans/second

**Wireless PAN**

Optional integrated Bluetooth™ compatible module (Serial Port Profile)

**Accessories**

**Communication/Charge Dock:** Single

RS-232, V90 Modem

**Multi-Dock:** Four Cavities (Daisy Chain) USB

Wrist Strap (Standard)

Scan Handle

Single Battery Charger

Cell Phone data cable

Printer cable

**Regulatory Approvals**

**Electrical:** CE Compliance

**Emissions:** FCC Part 15 – Class A

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.

\*Bluetooth is a trademark owned by Bluetooth SIG, Inc., USA.

**Intermec®**  
e x p e c t MORE™

**North America**

**Corporate Headquarters**  
6001 36<sup>th</sup> Avenue West  
Everett, Washington 98203  
tel: 425.348.2600  
fax: 425.355.9551

**Systems & Solutions**

550 2nd Street S.E.  
Cedar Rapids, Iowa 52401  
tel: 319.369.3100  
fax: 319.369.3453

**Media Supplies**

9290 Le Saint Drive  
Fairfield, Ohio 45014  
tel: 513.874.5882  
fax: 513.874.8487

**Canada**

7065 Tranmere Drive  
Mississauga, Ontario  
L5S 1M2 Canada  
tel: 905.673.9333  
fax: 905.673.3974

**Europe/****Middle East & Africa**

**Headquarters**  
Sovereign House  
Vastern Road  
Reading RG1 8BT  
United Kingdom  
tel: 44.118.987.9400  
fax: 44.118.987.9401

**Asia**

**Asia Regional Office**  
26-16 International Plaza  
10 Anson Road  
Singapore 079903  
tel: 65.6324.8391  
fax: 65.6324.8393

**Intermec International Inc**

14 Floor, IBM-Pacific Century Plaza  
2A Workers Stadium  
Chaoyang District, Beijing 100027  
P.R. China  
Tel: +86 (010).6539 1012  
Fax: +86 (010).6539 1025

**Australia**

Level 7, 200 Pacific Highway  
Crows Nest, NSW 2065  
Australia  
tel: 61.2.9492.4400  
fax: 61.2.9954.6300

**South America & Mexico**

**Intermec South America Ltda.**  
Rua Arandu 1544-15 andar  
Edifício Itavera  
Brooklin Novo 04562-031  
Sao Paulo, SP  
Brazil  
tel: 55.11.5501.2070

**Intermec Technologies de Mexico**

Av Tamaulipas #141, Primer Piso  
Col. Hipodromo Condesa  
Mexico, DF, 06140 Mexico  
tel: 525.55.211.1919  
fax: 525.55.211.8121

**Worldwide**

**Fax Document Retrieval Service**  
800.755.5505  
(North America Only)  
tel: 650.556.8447

**Internet**

www.intermec.com

**Sales**

800.347.2636  
(toll free in N.A.)  
tel: 425.348.2726

**Service and Support**

800.755.5505  
(toll free in N.A.)  
tel: 425.356.1799

Copyright © 2004 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611405-01B 05/04

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.