

The Intermec logo is positioned vertically on the left side of the page, featuring the word "Intermec" in a bold, blue, sans-serif font.

Product Profile

- Bluetooth™ radio communication eliminates cables and facilitates complete mobility
- Interfaces with Intermec terminals and personal computers
- Choice of Vista linear imager, area imager, or standard range laser scan options
- Easy configuration and personalization
- Industrial durability stands up to harsh environments
- Vehicle mount charger option



Intermec[®]
Intellibeam[™]



SR61 HANDHELD CORDLESS SCANNER

Intermec's SR61 handheld cordless scanner incorporates the flexibility and rugged design of a handheld scanner with the seamless functionality of wireless communication. The SR61 features a personal area network (PAN) radio based on Bluetooth™ communication protocol, making scanning easier and safer with no costly cables to damage or become entangled. Users gain hassle-free mobility up to 30 meters (100 feet) from the host!

With the ability to interface with Intermec computer products including the 700 Series, CK30, CK31, CK60, and CV60- the SR61 cordless scanner increases productivity while keeping costs down. Users can connect up to seven SR61 scanners to one host device enabling multiple people to scan items for inventory management, picking, shipping and receiving, cross docking, work-in-process, tool crib, and pallet tracking, all with ease.


With multiple scan options, including linear, area and standard range laser, the SR61 allows users to configure the scanner to meet the specific needs of

their environment, whether they include reading specific barcode symbologies, decoding poor quality or damaged barcodes with ease or the ability to capture signatures for proof of delivery and point of service applications.

The SR61 includes Intermec's EasySet™ software setup tool for easy configuration and personalization. The user can quickly set security options, select beeper tones and volumes, good read and error read responses, and many other customizations.

Scan intensive applications require reliable, accurate scanning and the SR61 delivers. The SR61 is designed to withstand rigorous application environments surviving multiple drops to concrete, cold and hot temperatures, and sealed to withstand dirt and water.

The SR61 delivers 10+ hours of use with a long lasting lithium ion battery that can be easily swapped ensuring minimal downtime. Multiple charging options include a vehicle mount charging cradle for forklift applications in warehouse environments.



Physical Characteristics

Length: 17.78 cm (7 in)
Width: 6.99 cm (2.75 in)
Depth: 11.43 cm (4.5 in)
Weight: 425 gm (15 oz)

Power

Battery Type: Lithium-ion
Battery Life: 10+ hours per full charge
Recharging Time: 2.5 hours for 90% charge

Connectivity

Bluetooth radio connection to Intermec computers including the 700 Series, CK30, CK60, CV60, and standard PCs.

Radio Characteristics

Frequency Band: 2.4 Ghz
Radio Type: Bluetooth Class 1 version 1.2
Radio Data Rate: 1 megabit per second

Radio Range

Host radio Class 1: 30.5 m (100 ft)
Host radio Class 2: 10 m (32.8 ft)
Features: Adaptive Frequency Hopping

Scan Engine Options

Standard range laser
 Vista linear imager
 Area imager

Scan Range**Linear Imager**

Bar Code Label Size	Scan Range
2 mil / 0.05 mm	8.8 to 12.6 cm
5 mil / 0.13 mm	5 to 20 cm
7.5 mil / 0.19 mm	2.5 to 34 cm
10 mil / 0.25 mm	2.5 to 36.7 cm
15 mil / 0.38 mm	2.5 to 50.6 cm
20 mil / 0.5 mm	2.5 to 63 cm
40 mil / 1.0 mm	5 to 102 cm
55 mil / 1.4 mm	7.6 to 102 cm
70 mil / 1.8 mm retro-reflective	23 to 91 cm
100 mil / 2.54 mm retro-reflective	30 to 106 cm
100% UPC/EAN	2.5 to 34 cm

Area Imager

Bar Code Label Size	Scan Range
5 mil / 0.125 mm	8.2 to 12.3 cm
6 mil / 0.15 mm	7.5 to 14.8 cm
8 mil / 0.20 mm	5.5 to 20.5 cm
10 mil / 0.25 mm	4.0 to 25.0 cm
12 mil / 0.30 mm	3.8 to 29.0 cm
20 mil / 0.5 mm	5.0 to 40.0 cm
40 mil / 1.0 mm	8.5 to 60.0 cm

Supported Bar Code Symbologies

1D (all versions): Code 128/EAN128; Code 39; Interleaved 2/5: UPC/EAN/ISBN including add-ons; 2/5 Matrix, standard; Codabar; Code 93; MSI; Plessey; Code 93i; Code 11; Telepen; ISBT128; RSS

Stacked (Vista and Area versions only): RSS; Micro PDF; PDF417; Macro PDF; Codablock; TLC39; Composite Codes (CC-A, B & C)

2D (Area version only): Maxicode; DataMatrix; QR Code; 4-State Postal Code; Planet Postal Code; Postnet Postal Code

Environment

Operating Temperature:
 -20°C to +50°C (-4°F to +122°F)

Storage Temperature:
 -20°C to +60°C (-4°F to +140°F)

Recharging Temperature:
 0°C to +45°C (32°F to +113°F)

Humidity: 0 to 95% RH, Non-condensing

Shock and Vibration Protection: SAE Specification J1399 Class 3 (off road vehicle)

Rain and Dust Resistance: IP-65

Drop Survival: 26 drops onto concrete or steel surface from a height of 1.98 meters (6.5 feet)

Ambient light: Works in any lighting conditions from 0 to 100,000 lux

Accessories

SR61 Dangle Suspension (wrist or fixed)
 Belt Holster
 Desktop / Wall Mount Charger
 2, 4 and 8 Bay Charger
 Vehicle Mount Charger
 Bluetooth USB Adapter
 Replacement Battery w/ Boot
 EasySet™ Configuration Utility

Regulatory Approvals

CISPR 22 Class B; Part 15 of FCC rules, Class B; CE Mark (EU) (EN 55024, EN 55022 Class B, IEC 60950-1, IEC 60825-1); cULus (Canada and the USA) (UL 60950-1); GS Mark (Germany) (EN 60950-1, EN 60825-1); NOM (Mexico); C-TICK (Australia and New Zealand) (AS/NZS 3548 based on CISPR22); CCC (China); Spring Mark (Singapore); MIC and EK marks (South Korea); ANATEL (Brazil)

**North America**

Corporate Headquarters
 6001 36th Avenue West
 Everett, Washington 98203
 tel: 425.348.2600
 fax: 425.355.9551

550 2nd Street S.E.
 Cedar Rapids, Iowa 52401
 tel: 319.369.3100
 fax: 319.369.3453

Media Supplies
 9290 Le Saint Drive
 Fairfield, Ohio 45014
 tel: 513.874.5882
 fax: 513.874.8487

Canada

7065 Tranmere Drive
 Mississauga, Ontario
 L5S 1M2 Canada
 tel: 905.673.9333
 fax: 905.673.3974

**Europe/
Middle East & Africa
Headquarters**

Reading International Business Park
 Basingstoke Road
 Reading RG2 6DD
 United Kingdom
 tel: 44.118.923.0800
 fax: 44.118.923.0801

Asia

Asia Regional Office
 26-16 International Plaza
 10 Anson Road
 Singapore 079903
 tel: 65.6324.8391
 fax: 65.6324.8393

Beijing Representative Office

29 FL, Unit A1, China Merchant Tower
 118 Jian Guo Road
 Chaoyang District, Beijing 100022
 Tel: 86.10.5165.5922
 Fax: 86.10.6567.6778

Australia

Level 4, 1-3 Atchison Street
 St. Leonards, NSW 2065
 Australia
 tel: 61.2.9330.4400
 fax: 61.2.9437.0204

South America & Mexico

Intermec South America Ltda.
 Rua Samuel Morse 120 9 andar
 Brooklin CEP04576-060
 São Paulo, SP
 Brazil
 tel: 55.11.5502.6770

Intermec Technologies de Mexico

Av Tamaulipas #141, Primer Piso
 Col. Hipodromo Condesa
 Mexico, DF, 06140 Mexico
 tel: 525.55.241.4800
 fax: 525.55.211.8121

Internet

www.intermec.com

Sales

800.934.3163
 (toll free in N.A.)
 tel: 425.348.2726

OEM Sales

tel: 425.348.2762

Customer Service and Support

800.755.5505
 (toll free in N.A.)
 tel: 425.356.1799

Copyright © 2006 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611734-01D 06/06

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.