

Product Profile

- Lightweight, rugged and weather resistant
- Palm sized form factor
- Resilient high density polyethylene
- Li-Ion batteries
- User downloadable character sets
- Windows® driver available
- Serial RS-232 interface
- 4MB of flash can be updated
- Sleep mode



6 8 1 / 6 8 2 P R I N T E R S & W O R K B O A R D S

Rugged and Affordable

The Intermec® 681 and 682 thermal and dot matrix printers are small, light durable units that can be used in even the most challenging delivery environments. They offer exceptional print clarity and versatility. These printers can quickly print both standard and bar coded receipts plus signature capture.

Intermec printers have the features that maximize portability and minimize size and the ability to withstand the rugged conditions of distribution applications. Their functional design makes paper loading easy and Lithium-Ion batteries offer maximum capacity power with reduced weight.

Compatible with Current Mobile Units

Both the 681T (thermal) and 681DM (dot matrix) portable printers are fully compatible with a wide variety of current model Intermec mobile computers including the 600, 6200 and 6100 Series of mobile computers.

Reliable Quality

The reliable printer mechanism of the Intermec 681/682 enables use in the most challenging delivery environment. This durability does not come at the expense of print quality, as the 681/682 printers offers exceptional print clarity and the versatility of graphics capability for logos and even bar codes.

Power to Spare

The automatic power saving sleep mode and quick three hour recharge time along with the vehicle charger option creates the optimum application solution for a long service day.

682T and 682DM Printer Workboards

Designed specifically to hold the Intermec 600 Series mobile computer, the 682T and 682DM printer workboards offer a rugged one piece solution. The 682T features a 40-column direct thermal printer while the 682DM features a 40-column dot matrix printer.

Both workboards accommodate a hand strap, shoulder strap or are capable of being mounted in a vehicle. Durable in design, these workboards easily take the punishment of daily work environments.

681T/681DM Printers Physical Characteristics**Length:** 143.5 mm (5.65")**Width:** 111.5 mm (4.39")**Depth:** 60.96 mm (2.40")**Weight:** 393 g (13.85 oz); 418 g (14.72 oz)**682T/682DM Printer Workboards****Physical Characteristics****Length:** 254.0 mm (10.00")**Width:** 179.32 mm (7.06")**Depth:** 60.96 mm (2.40")**Weight:** 645 g (22.72 oz); 668 g (23.52 oz)**Environment**

Operating Temperature:

681T: -20° to 50° C (-4° to 122° F)**681DM:** 0° to 50° C (32° to 122° F)**682T:** -20° to 50° C (-4° to 122° F)**682DM:** 0° to 50° C (32° to 122° F)**Power Source**

7.2V Lithium-Ion 1800 mAh (2) 3.8V cells in series

Battery Recharging

Nine hours to full charge using a vehicle charger power adapter or standard AC power adapter

Printer Mechanism Characteristics**681T/682T:** Direct thermal line printer 203 dots per inch (dpi)**681DM/682DM:** Impact dot matrix printer 240 dots per inch (dpi)**Print Speed****681T/682T:** 1.83" per second**681DM/682DM:** .33" per second**Fonts****Thermal:** Hundreds of fonts available.

Comes with seven (7) standard load fonts

Dot Matrix: Comes with two (2) standard load fonts**Print Capabilities**

Characters, graphics and bar codes

Paper Medium

Thermal paper, two-ply

Print Duration Per Charge

Dependent on usage and dot matrix or thermal printer engine. An 8-hour shift is easily accomplished.

Interface

IrDA®

RS-232 serial

Chargers

AC wall charger

12V vehicle charger

Regulatory Approvals

FCC Title 47, Part 15, Subpart B, Class B

EN55022 Class B

EN50082-1

IEC1000-3-2

IEC1000-3-3

Some approvals and features may vary by country and may change without notice. Specs may vary based upon the specific configuration or features selected. Please check with your local Intermec sales office for further information.

**North America**

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies
9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

Canada

7065 Tranmere Drive
Mississauga, Ontario
L5S 1M2 Canada
tel: 905.673.9333
fax: 905.673.3974

Europe/**Middle East & Africa**

Headquarters
Reading International Business Park
Basingstoke Road
Reading RG2 6DD
United Kingdom
tel: 44.118.923.0800
fax: 44.118.923.0801

Asia

Asia Regional Office
26-16 International Plaza
10 Anson Road
Singapore 079903
tel: 65.6324.8391
fax: 65.6324.8393

Beijing Representative Office

29 FL, Unit A1, China Merchant Tower
118 Jian Guo Road
Chaoyang District, Beijing 100022
Tel: 86.10.5165.5922
Fax: 86.10.6567.6778

Australia

Level 4, 1-3 Atchison Street
St. Leonards, NSW 2065
Australia
tel: 61.2.9330.4400
fax: 61.2.9437.0204

South America & Mexico

Intermec South America Ltda.
Rua Samuel Morse 120 9 andar
Brooklin CEP04576-060
São Paulo, SP
Brazil
tel: 55.11.5502.6770

Intermec Technologies de Mexico

Av Tamaulipas #141, Primer Piso
Col. Hipodromo Condesa
Mexico, DF, 06140 Mexico
tel: 525.55.241.4800
fax: 525.55.211.8121

Internet

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
tel: 425.348.2726

OEM Sales

tel: 425.348.2762

Service and Support

800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A.
609037-01F 12/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.