



Intermec

## Product Profile

- Lightweight, rugged, compact design
- Resilient high-density polyethylene case
- Companion to the Intermec® 700 Series Mobile Computer
- Integrated Bluetooth™ and 802.11 wireless printing
- Ability to perform wireless printer status and configuration requests
- Rated to withstand cold temperatures to -20° C
- External paper load option



### P B 4 1 P O R T A B L E P R I N T E R

Intermec's PB41 printer is the ultimate print solution for store delivery, route accounting, field service, logistics, home delivery and pre-sales systems. The PB41 interfaces seamlessly with the Intermec 700 Mobile Computer series. Daily route activities are easily entered and tracked via a mobile computer throughout a workers shift. Receipts are immediately provided to the customer for prompt payment or to eliminate duplicate billing efforts.

The lightweight and compact design of the PB41 is ideal for vehicle mounting or hand carrying. This printer is built to withstand the rugged conditions it will be exposed to on the road. The resilient high-density polyethylene case is virtually indestructible withstanding multiple four foot drops to concrete. The PB41 printer operates via vehicle mount or battery operation.

Spending a lot of time in cold environments? Intermec's PB41 direct thermal portable printer is rated to withstand temperatures as low as -20° C.

The PB41 can be used serially or wirelessly. The integrated Bluetooth and industry standard 802.11b wireless options make it easy for workers to remain on the go. There are no hassles with cables or wires. Bi-directional communication enables the printer to execute requests for wireless printer statuses and configuration. The printer goes where you need it, when you need it for maximum efficiency.

Intermec

**Application**

Direct Thermal receipt printing

**Physical Characteristics**

**Length:** 7.37 in (18.72 cm)  
**Height:** 6.82 in (17.32 cm)  
**Width:** 2.67 in (6.78 cm)  
**Weight:** 39.6 oz (1122.6 g) (incl. batteries / paper roll)  
**Drop Spec:** 4 feet (1.2 m)

**Print Specifications**

**Max. Print Width:** 4.09 in (104 mm)  
**Max. Print Length:** 120 feet is average roll size

**Print Speed**

Selectable print speeds up to 2.5 ips (63.5 mm)

**Print Resolution**

8 dots/mm (203.2 dpi)

**Media Specifications**

**Style:** Roll-feed continuous receipt or label  
**Type:** Direct thermal paper and labels  
**Max. Paper Width:** 4.41 in (112.0 mm)  
**Roll Capacity:** Thermal Paper: 1,716 in (43.5 m)

**Interface**

- RS-232 Serial – up to 115.2k baud
- Wireless LAN – Cisco Aironet® 350 Series PC Card (PCMCIA)
  - Frequency band: 2.4 to 2.4897 GHz
  - Data rates supported: 1, 2, 5.5, and 11Mbps
  - Network Standard: IEEE 802.11b
  - Network Architecture Types: Infrastructure and ad hoc
  - Wireless Medium: Direct Sequence Spread Spectrum (DSSS)
- Personal Area Network - Integrated Bluetooth Module
  - Network Environment: Ad hoc
  - Protocol: Supports version 1.1 of the Bluetooth standard (SIG certification pending)

**Power**

**Battery Type:** 7.2 V Lithium Ion 2,200 mAh (two batteries for a total of 4,400 mAh)

**DC Input:** 12-15V, built-in spike and surge protection

**Battery Life:** Dependent on usage -

- Bluetooth – prints 4,250 inches on a single battery charge
- 802.11b – Prints 3,864 inches on a single battery charge

**Recharging:** 2-3 hours from AC adapter or cigarette lighter adapter

**Bar Code Symbolologies**

Prints 1D and 2D bar codes

**Fonts**

5.5 CPI; 7.2 CPI; 10.2 CPI; 10.7 CPI; 18.5 CPI; 20.4 CPI; 22.6 CPI  
 Unicode subset including Thai and Latin

**Graphics**

Supports storage and one time transient use of graphics and logos in flash memory.

**Memory**

- Flash – 8 Mbit
- RAM – 4 Mbit

**Environment**

**Operating Temperature:**

-20° C to 50° C (-4° F to 122° F)

**Storage Temperature:**

-40° C to 70° C (-40° F to 158° F)

**Charging Temperature:**

5° C to 40° C (41° F to 104° F)

**Humidity:** 10% to 90% (non condensing)

**ESD Protection:** 8 kV Air, 4 kV Contact

**Regulatory Approvals**

FCC B, CE, C-Tick, E-Mark

**Warranty**

1 Year (including printer case)

**Options**

Swivel Belt Loop; Vehicle Mounting Bracket; DC Power Extension; AC Adapter; Cigarette Lighter Adapter; DB9F Data Cable



The Standard for Wireless Fidelity.

**Intermec®**  
 expect MORE®

**North America**

**Corporate Headquarters**  
 6001 36<sup>th</sup> Avenue West  
 Everett, Washington 98203  
 tel: 425.348.2600  
 fax: 425.355.9551

550 2nd Street S.E.  
 Cedar Rapids, Iowa 52401  
 tel: 319.369.3100  
 fax: 319.369.3453

**Media Supplies**  
 9290 Le Saint Drive  
 Fairfield, Ohio 45014  
 tel: 513.874.5882  
 fax: 513.874.8487

**Canada**

7065 Tranmere Drive  
 Mississauga, Ontario  
 L5S 1M2 Canada  
 tel: 905.673.9333  
 fax: 905.673.3974

**Europe/**

**Middle East & Africa  
 Headquarters**  
 Reading International Business Park  
 Basingstoke Road  
 Reading RG2 6DD  
 United Kingdom  
 tel: 44.118.923.0800  
 fax: 44.118.923.0801

**Asia**

**Asia Regional Office**  
 26-16 International Plaza  
 10 Anson Road  
 Singapore 079903  
 tel: 65.6324.8391  
 fax: 65.6324.8393

**Beijing Representative Office**

29 FL, Unit A1, China Merchant Tower  
 118 Jian Guo Road  
 Chaoyang District, Beijing 100022  
 Tel: 86.10.5165.5922  
 Fax: 86.10.6567.6778

**Australia**

Level 4, 1-3 Atchison Street  
 St. Leonards, NSW 2065  
 Australia  
 tel: 61.2.9330.4400  
 fax: 61.2.9437.0204

**South America & Mexico**

**Intermec South America Ltda.**  
 Rua Samuel Morse 120 9 andar  
 Brooklin CEP04576-060  
 São Paulo, SP  
 Brazil  
 tel: 55.11.5502.6770

**Intermec Technologies de Mexico**

Av Tamaulipas #141, Primer Piso  
 Col. Hipodromo Condesa  
 Mexico, DF, 06140 Mexico  
 tel: 525.55.241.4800  
 fax: 525.55.211.8121

**Internet**

www.intermec.com

**Sales**

800.347.2636  
 (toll free in N.A.)  
 tel: 425.348.2726

**OEM Sales**

tel: 425.348.2762

**Service and Support**

800.755.5505  
 (toll free in N.A.)  
 tel: 425.356.1799

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611533-01A 10/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.